

# GreenFlow AC Charger

Single Phase / Wall-mounted / 7 kW

## User-friendly Experience

- ▶ Start / end Charging via an RFID Card or Smart Mobile App
- ▶ OTA Updates

## Secure and Robust

- ▶ Suitable for Outdoor Environment
- ▶ Embedded RCD

## Smart Charging

- ▶ Scheduled Pre-set Charging
- ▶ Compatible with Most EVs



MODEL	CAS7
<b>Product Information</b>	
Input Wiring	1P+N+PE
Rated Power	7 kW
Rated Input Voltage	230 V AC ±15%
Rated Current	32 A
Charging Mode	Mode 3
Network Type	TT, TN
Connector Type	IEC 62196 Type 2 Plug, 5 m
Protection	Over-voltage protection, under-voltage protection, short circuit protection, grounding protection, over temperature protection, lightning protection
Dimensions (W x H x D)	216 x 268 x 105 mm
Frequency	50 ~ 60 Hz
RCD	6 mA DC + 30 mA Type A
Metering	On-Board Measurement
Card Reader	Mifare ISO / IEC14443 Type A
<b>General Characteristics</b>	
Activation Method	Plug n' Charge & RFID Card & App
App Function	Remote start & stop, Scheduled Charging, Real-time Monitoring, Data Display, Power Adjusting
Operating Altitude	< 2000 m
Operating Temperature	-30°C ~ +50°C
Storage Temperature	-40°C ~ +50°C
Operating Humidity	5% ~ 95%
Communication	WIFI + Bluetooth
LED	RGB LED
IP Rating	IP65
IK Rating	IK10
Certification	CE
EMC	Class B
IEC Standard	EN IEC 61851-1:2019 IEC61851-1:2017 IEC61851-21-2:2021
Warranty	2 Years