

BluePulse Series

KAC(80~125)DP2 - BC208DLE / BC260DLE

Extreme Safety & Reliability

- ▶ Tier 1 battery cell brand ensure high quality
- ▶ 4+3 fire safety design avoids fire risks
- ▶ Integrated intelligence temperature control

Versatile Adaptability

- ▶ 10ms-level* on / off grid switching time with integrated STS
- ▶ Max. 20 PCS parallel for on-grid, 10 PCS for on / off-grid situation
- ▶ Flexible expansion up to 10.4 MWh

Intelligent & User-friendly

- ▶ 3S (PCS, BMS, EMS) full-stack self-developed
- ▶ Integrated monitoring and O&M through KSTAR Sync
- ▶ VPP ready with KSTAR Sync Cloud



Liquid-cooling Battery Cabinet Parameters

Technical Parameters	BC208DLE	BC260DLE
Battery Type	LiFe (LiFePO4)	
Battery Module Capacity	52.24 kWh	
Number of Modules	4	5
Total Battery Capacity	208.99 kWh	261.24 kWh
Nominal Voltage	665.5 V	832 V
Operating Voltage Range	592.8 ~ 748.8 V	741 ~ 936 V
Max. Charge / Discharge Rate	0.5 C	
Standard Charging / Discharging Current	157 A / 157 A	
DoD	95%	
General Parameters		
Dimensions (W x H x D)	1040 x 2234 x 1370 mm	
Weight	< 2.5 T	
Installation Site	Outdoor	
IP Protection	IP54	
Anti Corrosion Level	C4	
Operation Humidity	5% ~ 95% (No Condensing)	
Operation Temperature	-30°C ~ +50°C	
Max. Operation Altitude	≤ 3000 m (>2000m Derating)	
Communication Port	Ethernet; CAN	
Communication Protocol	CAN; TCP	
Cooling Method	Liquid Cooling	
Warranty	5 Year Product Warranty, 10 Year Performance Warranty	
Certificates	UN38.3; MSDS; IEC 62040; IEC 62477; IEC 62619; IEC 63056; IEC 61000-6-2/4	

* The 10ms on / off-grid switching time applies to single-PCS operation with a purely resistive load.

Hybrid Inverter Parameters

Product Specifications	KAC80DP2		KAC100DP2	KAC110DP2	KAC125DP2
PV Side					
MPPT Voltage Range	250 ~ 950 V (Max. 1000 V)				
MPPT Rated Voltage	720 V				
MPPT Rated Voltage (Full Load)	450 ~ 800 V	550 ~ 800 V	600 ~ 800 V	700 ~ 800 V	
Max. PV Power	160 kWp	200 kWp	220 kWp	250 kWp	
Number of MPPT / Strings per MPPT	8 / 2				
Max. Current per MPPT	45 A				
Battery Side					
Battery Voltage Range	200 ~ 950 V				
Battery Rated Voltage Range	250 ~ 850 V				
Max. DC Current	160 A (80 A x 2)				
Max. DC Power	88 kW	110 kW	121 kW	125 kW	
Number of DC Inputs	2				
AC Side (On Grid)					
Nominal AC Output Power	80 kW	100 kW	110 kW	125 kW	
Max. AC Output Power	88 kVA	110 kVA	121 kVA	125 kVA	
Rated AC Output Current	116 A	144 A	159 A	181 A	
Max.AC Input Current	227 A	227 A	227 A	227 A	
AC Rated Voltage / Voltage Range	230 / 400 Vac; 220 / 380 Vac; 3L+PE+N; -15% ~ +10%				
Nominal Grid Frequency / Frequency Range	50 Hz / 60 Hz (±5 Hz)				
THDi	< 3% (100% Load)				
Adjustable PF Range	0.8 inductive(under-excited) to 0.8 capacitive(over-excited)				
Backup Output					
Nominal AC Voltage	230 / 400 V; 220 / 380 Vac; 3L+PE+N				
THDv	< 3% (Rated Power)				
Nominal Grid Frequency / Frequency Range	50 Hz / 60 Hz				
Nominal AC Output Power	80 kW	100 kW	110 kW	125 kW	
Max. AC Output Power (Single-phase)	50 kW				
Max. Output Current	227 A				
Genset Input					
Max. Input Current	227 A				
Efficiency					
Max. Efficiency	98%				
Protection					
Reverse DC Connection Protection	Yes				
Anti-Islanding Protection	Yes				
Over-Temperature Protection	Yes				
Grid Monitoring / Earthing Fault Detection	Yes				
Insulation Monitoring	Yes				
DC / AC Surge Protection	DC Type II; AC Type II				
AFCI	Optional				
General Parameters					
Dimensions (W x H x D)	1120 x 760 x 365 mm				
Weight	135 kg				
Topology	Transformerless				
IP Protection	IP66				
Operation Temperature Range	-30 ~ 60°C (> 45°C Derating)				
Operation Humidity Range	0 ~ 100% (No Condensing)				
Cooling Method	Intelligent Air Cooling				
Max. Operation Altitude	4000 m (> 3000 m Derating)				
Communication Port	RS-485 / CAN				