

BluePulse Series NEW

KAC80DP2 / KAC100DP2 / KAC110DP2 / KAC125DP2
BC208DLE / BC260DLE

Extreme Safety & Reliability

- ▶ Tier 1 battery cell brand ensure high quality
- ▶ 4+3 fire safety design avoids fire risks
- ▶ Integrated intelligence temperature control

Versatile Adaptability

- ▶ Multi-scenario adaptation & Flexible solution configuration
- ▶ Scalable up to 10.4 MWh
- ▶ Floor space reduced by 25%

Intelligent & User-friendly

- ▶ 3S (PCS, BMS, EMS) full-stack self-developed
- ▶ Integrated monitoring and O&M through KSTAR Sync
- ▶ VPP ready with KSTAR Sync Cloud



Liquid-cooling Battery Cabinet Parameters

Technical Parameters	BC208DLE	BC260DLE
Battery Type	LiFe (LiFePO4)	
Battery Module Capacity	52.24 kWh	
Number of Modules	4	5
Total Battery Capacity	208.99 kWh	261.24 kWh
Nominal Voltage	665.5 V	832 V
Operating Voltage Range	592.8 ~ 748.8 V	741 ~ 936 V
Charge / Discharge Rate	0.5 C	
Standard Charging / Discharging Current	157 A / 157 A	
DoD	90%	
General Parameters		
Dimensions (W x H x D)	1040 x 1370 x 2234 mm	
Weight	< 2.5 T	
Installation Site	Outdoor	
IP Protection	IP54	
Anti Corrosion Level	C4	
Operation Humidity	5% ~ 95% (No Condensing)	
Operation Temperature	-20°C ~ +50°C	
Max. Operation Altitude	≤ 3000 m (>2000m Derating)	
Communication Port	Ethernet; CAN	
Communication Protocol	CAN; TCP	
Cooling Method	Liquid Cooling	
Warranty	5 Year Product Warrantant,10 Year Performance Warranty	
Certification	UN38.3; MSDS; IEC 62040; IEC 62477; IEC 62619; IEC 63056; IEC 61000-6-2/4	

Hybrid Inverter Parameters

Product Specifications	KAC80DP2	KAC100DP2	KAC110DP2	KAC125DP2
PV Side				
MPPT Voltage Range	250 ~ 950 V (Max. 1000 V)			
MPPT Rated Voltage	720 V			
MPPT Rated Voltage (Full Load)	450 ~ 800 V	550 ~ 800 V	600 ~ 800 V	700 ~ 800 V
Max. PV Power	160 kWp	200 kWp	220 kWp	250 kWp
Number of MPPT / Strings per MPPT	8 / 2			
Max. Current per MPPT	45 A			
Battery Side				
Battery Voltage Range	200 ~ 950 V			
Battery Rated Voltage Range	250 ~ 850 V			
Max. DC Current	160 A (80 A x 2)			
Max. DC Power	88 kW	110 kW	121 kW	125 kW
Number of DC Inputs	2			
AC Side (On Grid)				
Nominal AC Output Power	80 kW	100 kW	110 kW	125 kW
Max. AC Output Power	88 kVA	110 kVA	121 kVA	125 kVA
Rated AC Current	116 A	144 A	159 A	181 A
Max. AC Current	227 A			
AC Rated Voltage / Voltage Range	230 / 400 Vac; 220 / 380 Vac; 3L+PE+N; -15% ~ +10%			
Nominal Grid Frequency / Frequency Range	50 Hz / 60 Hz (±5 Hz)			
THDi	< 3% (100% Load)			
Adjustable PF Range	0.8 inductive(under-excited) to 0.8 capacitive(over-excited)			
Backup Output				
Nominal AC Voltage	230 / 400 V; 220 / 380 Vac; 3L+PE+N			
THDv	< 3% (Rated Power)			
Nominal Grid Frequency / Frequency Range	50 Hz / 60 Hz			
Nominal AC Output Power	80 kW	100 kW	110 kW	125 kW
Max. AC Output Power (Single-phase)	50 kW			
Max. Output Current	227 A			
Genset Input				
Max. Input Current	227 A			
Efficiency				
Max. Efficiency	98%			
Protection				
Reverse DC Connection Protection	Yes			
Anti-Islanding Protection	Yes			
Over-Temperature Protection	Yes			
Grid Monitoring / Earthing Fault Detection	Yes			
Insulation Monitoring	Yes			
DC / AC Surge Protection	DC Type II; AC Type II			
AFCI	Optional			
General Parameters				
Dimensions (W x H x D)	1120 x 760 x 365 mm			
Weight	135 kg			
Topology	Transformerless			
IP Protection	IP66			
Operation Temperature Range	-25 ~ 60°C (> 45°C Derating)			
Operation Humidity Range	0 ~ 100% (No Condensing)			
Cooling Method	Intelligent Air Cooling			
Max. Operation Altitude	4000 m (> 3000 m Derating)			
Communication Port	RS-485 / CAN			