



Product Service

Compliance Document

No. D 075386 0334 Rev. 00

Holder of Attestation: **Shenzhen Kstar New Energy Company Limited**

The 9th Floor, R&D Building
Kstar Industrial Park, Guangming Hi-tech Industrial Zone
518107 Shenzhen, Guangdong Province
PEOPLE'S REPUBLIC OF CHINA

Product: **Converter**
(Energy Storage Inverter & Hybrid Inverter)

Model(s): **Hybrid Inverter:**
KAC125DP2, KAC110DP2, KAC100DP2,
KAC80DP2, KAC125DP2-S0,
KAC110DP2-S0, KAC100DP2-S0,
KAC80DP2-S0,

Energy Storage Inverter:
KAC125D2, KAC110D2, KAC100D2,
KAC80D2, KAC125D2-S0, KAC110D2-S0,
KAC100D2-S0, KAC80D2-S0

Parameters: See page 2 to 5

Tested according to: TOR Stromerzeugungsanlagen Typ B Version 1.3:2024

This Compliance document confirms the compliance with the listed standards on a voluntary basis. It refers only to the particular sample. This compliance document makes no statement regarding the quality or safety of the serial products. For details see: www.tuvsud.com/ps-cert

Test report no.: 64290253196801

Date, 2026-03-24

Kennen Wang

(Kennen Wang)



Product Service

Compliance Document

No. D 075386 0334 Rev. 00

Parameters:

Model	KAC125DP2	KAC110DP2	KAC100DP2	KAC80DP2
PV terminal parameters				
Maximum input voltage [V _{DC}]	1000	1000	1000	1000
Rated input voltage [V _{DC}]	720	720	720	720
MPPT voltage range (full load) [V _{DC}]	700-800	660-800	620-800	550-800
MPPT tracker number	8	8	8	8
Maximum input current [A _{DC}]	45*8	45*8	45*8	45*8
Isc PV [A _{DC}]	60*8	60*8	60*8	60*8
Maximum input power [W]	250000	200000	200000	160000
Battery input/output parameters				
Battery type	Lithium-ion	Lithium-ion	Lithium-ion	Lithium-ion
Battery rated voltage [V _{DC}]	820	820	820	820
Battery voltage range (full load) [V _{DC}]	820-890	730-890	730-890	580-890
Maximum charge power [W]	125000	110000	110000	88000
Maximum discharge power [W]	125000	110000	110000	88000
Maximum charge current [A _{DC}]	80/80	80/80	80/80	80/80
Maximum discharge current [A _{DC}]	80/80	80/80	80/80	80/80
Grid terminal input parameters				
Rated input voltage [V _{AC}]	3P+N+PE, 230/400	3P+N+PE, 230/400	3P+N+PE, 230/400	3P+N+PE, 230/400
Rated input frequency [Hz]	50	50	50	50
Maximum continuous input current [A _{AC}]	217	217	217	217
Maximum continuous input power from grid to battery [W]	125000	110000	110000	88000
Maximum continuous input active power [W]	150000	150000	150000	150000
Maximum continuous input apparent power [VA]	150000	150000	150000	150000
Power factor range	0.9 inductive(under-excited) to 0.9 capacitive(over-excited)			
Grid terminal output parameters				
Rated output voltage [V _{AC}]	3P+N+PE, 230/400	3P+N+PE, 230/400	3P+N+PE, 230/400	3P+N+PE, 230/400
Rated output frequency [Hz]	50	50	50	50
Rated output current [A _{AC}]	199	175	160	127
Design active power P _D [W]	123750	108900	99000	79200
Rated output active power [W]	125000	110000	100000	80000
Maximum output active power [W]	125000	110000	100000	80000
Maximum continuous output apparent power [VA]	137500	121000	110000	88000
Power factor range	0.9 inductive(under-excited) to 0.9 capacitive(over-excited)			



Product Service

Compliance Document

No. D 075386 0334 Rev. 00

Model	KAC125DP2-S0	KAC110DP2-S0	KAC100DP2-S0	KAC80DP2-S0
PV terminal parameters				
Maximum input voltage [V _{DC}]	1000	1000	1000	1000
Rated input voltage [V _{DC}]	720	720	720	720
MPPT voltage range (full load) [V _{DC}]	700-800	660-800	620-800	550-800
MPPT tracker number	8	8	8	8
Maximum input current [A _{DC}]	45*8	45*8	45*8	45*8
Isc PV [A _{DC}]	60*8	60*8	60*8	60*8
Maximum input power [W]	250000	200000	200000	160000
Battery input/output parameters				
Battery type	Lithium-ion	Lithium-ion	Lithium-ion	Lithium-ion
Battery rated voltage [V _{DC}]	820	820	820	820
Battery voltage range (full load) [V _{DC}]	820-890	730-890	730-890	580-890
Maximum charge power [W]	125000	110000	110000	88000
Maximum discharge power [W]	125000	110000	110000	88000
Maximum charge current [A _{DC}]	80/80	80/80	80/80	80/80
Maximum discharge current [A _{DC}]	80/80	80/80	80/80	80/80
Grid terminal input parameters				
Rated input voltage [V _{AC}]	3P+N+PE, 230/400	3P+N+PE, 230/400	3P+N+PE, 230/400	3P+N+PE, 230/400
Rated input frequency [Hz]	50	50	50	50
Maximum continuous input current [A _{AC}]	199	175	160	127
Maximum continuous input power from grid to battery [W]	125000	110000	110000	88000
Maximum continuous input active power [W]	125000	110000	110000	88000
Maximum continuous input apparent power [VA]	137500	121000	110000	88000
Power factor range	0.9 inductive(under-excited) to 0.9 capacitive(over-excited)			
Grid terminal output parameters				
Rated output voltage [V _{AC}]	3P+N+PE, 230/400	3P+N+PE, 230/400	3P+N+PE, 230/400	3P+N+PE, 230/400
Rated output frequency [Hz]	50	50	50	50
Rated output current [A _{AC}]	199	175	160	127
Design active power P _D [W]	123750	108900	99000	79200
Rated output active power [W]	125000	110000	100000	80000
Maximum output active power [W]	125000	110000	100000	80000
Maximum continuous output apparent power [VA]	137500	121000	110000	88000
Power factor range	0.9 inductive(under-excited) to 0.9 capacitive(over-excited)			



Product Service

Compliance Document

No. D 075386 0334 Rev. 00

Model	KAC125D2	KAC110D2	KAC100D2	KAC80D2
Battery input/output parameters				
Battery type	Lithium-ion	Lithium-ion	Lithium-ion	Lithium-ion
Battery rated voltage [V _{DC}]	820	820	820	820
Battery voltage range (full load) [V _{DC}]	820-890	730-890	730-890	580-890
Maximum charge power [W]	125000	110000	110000	88000
Maximum discharge power [W]	125000	110000	110000	88000
Maximum charge current [A _{DC}]	80/80	80/80	80/80	80/80
Maximum discharge current [A _{DC}]	80/80	80/80	80/80	80/80
Grid terminal input parameters				
Rated input voltage [V _{AC}]	3P+N+PE, 230/400	3P+N+PE, 230/400	3P+N+PE, 230/400	3P+N+PE, 230/400
Rated input frequency [Hz]	50	50	50	50
Maximum continuous input current [A _{AC}]	217	217	217	217
Maximum continuous input power from grid to battery [W]	125000	110000	110000	88000
Maximum continuous input active power [W]	150000	150000	150000	150000
Maximum continuous input apparent power [VA]	150000	150000	150000	150000
Power factor range	0.9 inductive(under-excited) to 0.9 capacitive(over-excited)			
Grid terminal output parameters				
Rated output voltage [V _{AC}]	3P+N+PE, 230/400	3P+N+PE, 230/400	3P+N+PE, 230/400	3P+N+PE, 230/400
Rated output frequency [Hz]	50	50	50	50
Rated output current [A _{AC}]	199	175	160	127
Design active power P _D [W]	123750	108900	99000	79200
Rated output active power [W]	125000	110000	100000	80000
Maximum output active power [W]	125000	110000	100000	80000
Maximum continuous output apparent power [VA]	137500	121000	110000	88000
Power factor range	0.9 inductive(under-excited) to 0.9 capacitive(over-excited)			



Product Service

Compliance Document

No. D 075386 0334 Rev. 00

Model	KAC125D2-S0	KAC110D2-S0	KAC100D2-S0	KAC80D2-S0
Battery input/output parameters				
Battery type	Lithium-ion	Lithium-ion	Lithium-ion	Lithium-ion
Battery rated voltage [V _{DC}]	820	820	820	820
Battery voltage range (full load) [V _{DC}]	820-890	730-890	730-890	580-890
Maximum charge power [W]	125000	110000	110000	88000
Maximum discharge power [W]	125000	110000	110000	88000
Maximum charge current [A _{DC}]	80/80	80/80	80/80	80/80
Maximum discharge current [A _{DC}]	80/80	80/80	80/80	80/80
Grid terminal input parameters				
Rated input voltage [V _{AC}]	3P+N+PE, 230/400	3P+N+PE, 230/400	3P+N+PE, 230/400	3P+N+PE, 230/400
Rated input frequency [Hz]	50	50	50	50
Maximum continuous input current [A _{AC}]	199	175	160	127
Maximum continuous input power from grid to battery [W]	125000	110000	110000	88000
Maximum continuous input active power [W]	125000	110000	110000	88000
Maximum continuous input apparent power [VA]	137500	121000	110000	88000
Power factor range	0.9 inductive(under-excited) to 0.9 capacitive(over-excited)			
Grid terminal output parameters				
Rated output voltage [V _{AC}]	3P+N+PE, 230/400	3P+N+PE, 230/400	3P+N+PE, 230/400	3P+N+PE, 230/400
Rated output frequency [Hz]	50	50	50	50
Rated output current [A _{AC}]	199	175	160	127
Design active power P _D [W]	123750	108900	99000	79200
Rated output active power [W]	125000	110000	100000	80000
Maximum output active power [W]	125000	110000	100000	80000
Maximum continuous output apparent power [VA]	137500	121000	110000	88000
Power factor range	0.9 inductive(under-excited) to 0.9 capacitive(over-excited)			